



## RFB LATEX LIMITED

### Specifications For Neoprene Black Flocklined Gloves

#### PHYSICAL DIMENSIONS

Size	Minimum Length in mm	Width in mm	Minimum Thickness in mm			Weight
			Cuff	Palm	Finger	Grams/pr
Small	300	105 ± 5	0.40	0.50	0.70	42
Medium	300	115 ± 5	0.40	0.50	0.70	44
Large	300	125 ± 5	0.40	0.50	0.70	46
X Large	300	135 ± 5	0.40	0.50	0.70	48

#### PHYSICAL REQUIREMENTS

Properties	Before Aging	After Aging
Tensile Strength, minimum	10 mpa	7 mpa
Ultimate Elongation, minimum	500%	375%

#### TEST RESULTS

Property	Test Method	Result
1000ml water leak test	ASTM D 5151	Complies with an AQL of 1.5 at General Inspection Level – 1
Resistance against Penetration	EN 374-2	Complies with an AQL of 1.5 at General Inspection Level-1
Resistance against permeation	EN 374-3	<i>Performance Level – 6</i> <i>Performance Level - 2</i> <i>Performance Level – 2</i>
<i>Methanol</i>		
<i>NaOH 40%</i>		
<i>H<sub>2</sub>SO<sub>4</sub> 96%</i>		
Abrasion , Blade Cut ,Tear, Puncture Resistance	EN388	0010
General Requirements/design	EN 420	Complies
Sizes / measures	EN 420	Complies
Dexterity / handling	EN 420	Class – 5

Design	Hand Specific, Curved fingers, textured finish with embossed pattern on the finger and palm surface (front side only).
Cuff	Beaded/Non Beaded
Colour	Black Colour with white Flocklined base in side
Quality Assurance	Manufactured under Good Manufacturing Practice (GMP) and ISO 9001 Quality Systems.

